





X - R16

Article	Article-No.	 [mm]	 [mm]	 [g]		
R16 tool	300	-	5-16	145		
set of rollers (3 pcs)	301	0.5	5-16	19		
 <p>metric DIN ISO 13</p>	302	0.75	5-16	19		
	303	0.8	5-16	19		
	304	1.0	5-16	19		
	305	1.25	5-16	19		
	306	1.5	5-16	19		
	307	1.75	5-16	19		
	308	2.0	5-16	19		
	301.1	0.5 LH	5-16	19		
	302.1	0.75 LH	5-16	19		
	303.1	0.8 LH	5-16	19		
	304.1	1.0 LH	5-16	19		
	305.1	1.25 LH	5-16	19		
	306.1	1.5 LH	5-16	19		
	307.1	1.75 LH	5-16	19		
	308.1	2.0 LH	5-16	19		
	<p>UNC/UNF/UNEF ANSI B1.1</p>		Threads per inch (TPI)			
		321	32	5-16	19	
		322	28	5-16	19	
323		24	5-16	19		
324		20	5-16	19		
325		18	5-16	19		
326		16	5-16	19		
327		14	5-16	19		
328		13	5-16	19		
329		12	5-16	19		
330		11	5-16	19		
<p>BSW/BSF/BSPP BS84/ DIN ISO 228</p>	341	32	5-16	19		
	342	28	5-16	19		
	343	26	5-16	19		
	344	24	5-16	19		
	345	20	5-16	19		
	346	19	5-16	19		
	347	18	5-16	19		
	348	16	5-16	19		
	349	14	5-16	19		
	350	12	5-16	19		
	351	11	5-16	19		
G (BSP) DIN ISO 228	360	28	5-16	19		
	361	19	5-16	19		

Any further pitch for any thread type available on request. Contact us any time: ask@silbertool.com