





X - R60/R110

Article	Article-No.	 [mm]	 [mm]	 [g]		
R60 tool	100	-	M10-M60	1210		
R110 tool	10	-	M50-M110	1390		
set of rollers (3 pcs)	101	0.5	10-110	345		
 <p>metric DIN ISO 13</p>	102	0.8	10-110	345		
	103	1	10-110	345		
	104	1.25	10-110	345		
	105	1.5	10-110	345		
	106	1.75	10-110	345		
	107	2	10-110	345		
	108	2.5	10-110	345		
	109	3	10-110	345		
	101.1	0.5 LH	10-110	345		
	102.1	0.8 LH	10-110	345		
	103.1	1 LH	10-110	345		
	104.1	1.25 LH	10-110	345		
	105.1	1.5 LH	10-110	345		
	106.1	1.75 LH	10-110	345		
	107.1	2 LH	10-110	345		
	108.1	2.5 LH	10-110	345		
	109.1	3 LH	10-110	345		
	<p>UNC/UNF/UNEF ANSI B1.1</p>		Threads per inch (TPI)			
		121	28	10-110	345	
122		24	10-110	345		
123		20	10-110	345		
124		18	10-110	345		
125		16	10-110	345		
126		14	10-110	345		
127		12	10-110	345		
128		11	10-110	345		
129		10	10-110	345		
130	9	10-110	345			
<p>BSW/BSF/BSPP BS84/ DIN ISO 228</p>	141	19	10-110	345		
	142	18	10-110	345		
	143	16	10-110	345		
	144	14	10-110	345		
	145	12	10-110	345		
	146	11	10-110	345		
	147	10	10-110	345		
	148	9	10-110	345		
<p>G (BSP) DIN ISO 228</p>	160	19	10-110	345		
	161	14	10-110	345		
	162	11	10-110	345		

Any further pitches for any thread type available on request. Contact us any time: ask@silbertool.com